



EVF

High-power front loaded flying sub woofer

- 15” Low Frequency front loaded bass element.
- Very linear frequency response from 46Hz to 124Hz
- 18mm / 13 ply birch plywood with internal reinforced steel rigging hardware top and bottom.
- Black textured paint
- optional flying hardware
- Input phoenix panel to handle up to 10AWG connector
- 22 x 10M threaded suspension points
- 150W- 100V/70V Line transformer optional
- ANSI /IEC 60529 – IP44
- Maximum sustained humidity <80%
- Salt content of normal air <20%
- Galvanneal grill with vinyl coated acoustic screen and stainless steel Fasteners

Technical specifications:

| | |
|---|---------------------------------------|
| Frequency response (-3dB): | 67Hz – 95 Hz |
| Frequency response (-10dB): | 46 Hz – 125 Hz |
| Axial Sensitivity (1W/1Mtr) | 103 dB |
| Maximum Calc. SPL | 135 dB |
| Power Handling | 400 W Cont / 1600W Peak |
| Nominal impedance – Passive / Bi-amped | 4 Ohms Passive 8 Ohms Bi-amped |
| Minimum impedance – Passive / Bi-amped | 3.4 Ohms Passive 6.4 Ohms Bi-amped |
| Connectors | Phoenix 10 AWG terminals |
| Dimensions | 768 x 470 x 467 mm |
| Weight | max. 28.4 kg |

Make: Electro Voice or equivalent
 Type: EVF1151S-BLK
 Delivery and mounting ready for operation

Make offered:
 Type: