



EVF

High-power front loaded flying sub woofer

- 15” Low Frequency front loaded bass element.
- Very linear frequency response from 46Hz to 124Hz
- 150W- 100V/70V Line transformer optional
- 13-ply birch plywood
- Black textured paint
- Stainless steel grill and stainless steel Fasteners
- full-face protected by a powder-coated steel-front-grille backed with acoustic foam
- two multi pin phoenix connectors
- ANSI /IEC 60529 – IP55
- Maximum sustained humidity <80%

Technical specifications:

Frequency response (-3dB):	67Hz – 95 Hz
Frequency response (-10dB):	46 Hz – 125 Hz
Axial Sensitivity (1W/1Mtr)	103 dB
Maximum Calc. SPL	135 dB
Power Handling	400 W Cont / 1600W Peak
Nominal impedance – Passive / Bi-amped	4 Ohms Passive 8 Ohms Bi-amped
Minimum impedance – Passive / Bi-amped	3.4 Ohms Passive 6.4 Ohms Bi-amped
Connectors	Phoenix 10 AWG terminals
Dimensions	768 x 470 x 467 mm
Weight	max. 28.4 kg

Make: Electro Voice or equivalent
 Type: EVF1151S PIB
 Delivery and mounting ready for operation

Make offered:
 Type: