



EVF

High-power front loaded flying sub woofer

- 18” Low Frequency front loaded bass element.
- Very linear frequency response from 28Hz to 650Hz
- 18mm / 13 ply birch plywood with internal reinforced steel rigging hardware top and bottom.
- Black textured paint
- optional flying hardware
- Input phoenix panel to handle up to 10AWG connector
- 22 x 10M threaded suspension points
- 150W- 100V/70V Line transformer optional
- ANSI /IEC 60529 – IP44
- Maximum sustained humidity <80%
- Salt content of normal air <20%
- Galvanneal grill with vinyl coated acoustic screen and stainless steel Fasteners

Technical specifications:

Frequency response (-3dB):	35Hz – 100 Hz
Frequency response (-10dB):	28 Hz – 650 Hz
Axial Sensitivity (1W/1Mtr)	99 dB
Maximum Calc. SPL	131 dB
Power Handling	400 W Cont / 1600W Peak
Nominal impedance –	8 Ohms
Minimum impedance –	6 Ohms
Connectors	Phoenix 10 AWG terminals
Dimensions	768 x 675 x 726 mm
Weight	max. 46 kg

Make: Electro Voice or equivalent
 Type: EVF1181S-BLK
 Delivery and mounting ready for operation

Make offered:
 Type: