



# EVF

High-power front loaded flying sub woofer

- Dual 15" Low Frequency front loaded bass element.
- Very linear frequency response from 41Hz to 330Hz
- White textured paint
- full-face protected by a powder-coated steel-front-grille backed with acoustic foam
- Two multi pin phoenix connectors
- ANSI /IEC 60529 – IP55
- Maximum sustained humidity < 95%
- Salt content of normal air exposure <70%
- Stainless steel grill and stainless steel Fasteners
- Single Amp channel powered design
- Fiberglass enclosure
- Direct exposure to sun and rain , heavy rain , fog & snow

Technical specifications:

Frequency response (-3dB):	40Hz – 2600 Hz
Frequency response (-10dB):	30 Hz – 3200 Hz
Axial Sensitivity ( 1W/1Mtr)	101 dB
Maximum Calc. SPL	137 dB
Power Handling	1000 W Cont / 4000W Peak
Nominal impedance –	4 Ohms
Minimum impedance –	2.7 Ohms
Connectors	Phoenix 10 AWG terminals
Dimensions	768 x 675 x 726 mm
Weight	max. 53.1 kg

Make: Electro Voice or equivalent  
 Type: EVF2151D FGW  
 Delivery and mounting ready for operation

Make offered: .....  
 Type: .....