



EVID

Subwoofer Ceiling Speaker System

- 240 mm (10") bass with a moisture-resistant special membrane in a vented enclosure
- conic, wide coverage
- integrated crossover with passive limiter for the protection of the crossover and the LF-chassis
- due to a serially integrated transformer, the system is compatible for low-frequency operation as well as for connection to 100-V-systems
- rotary switch at front for the assignment of the operation mode (100-V-system / LF), i.e. operation mode and power adjustment can be determined after installation and cabling
- baffle and enclosure of heat-resistant ABS-synthetics according to UL 94V-0
- semi-gloss white perforated metal plate made of powder-coated steel, protected from falling by a special nylon rope
- enclosure of zinc-plated steel with a loop on the rear for additional safeguard mounting
- on the rear panel: 4-pin connector block for the connection of speakers and for the loop-through of signals to further speakers
- easy installation with enclosed mounting material (template for ceiling cutout, prolonged mounting angle for raster ceilings) for different mounting situations
- also furnished: special painting template for painting of the front frame

Technical specifications:

Frequency response (-10dB)	45 Hz to 180 Hz
Nominal coverage (-6 dB)	180°
Maximum long-term average power-handling capacity (per IEC 268-5)	150 W
Sensitivity (1W/1m),	94 dB
Max. SPL (1m)	120 dB
Nominal impedance	8 Ohm (transformer bypass)
Transformer taps	100V: 3.75, 7.5, 15 or 30 W Bypass: 8 Ohm
Dimensions (H x Ø)	303 x 320 mm (front panel : 350 mm)
Cutout size	324 mm
Weight	7.0 kg

Make: Electro Voice or equivalent
 Type: EVID C10.1
 Delivery and mounting ready for operation

Make offered:



EVID

Type: