



EVID

Co-axial 2-way Ceiling Speaker System

- 200 mm (12") mid-bass driver with a moisture-resistant special membrane in a vented enclosure
- 25 mm (1") swivel HF-transducer with titanium coating and a horn in co-axial array for symmetric coverage
- linear frequency response and conic, very wide and even coverage
- integrated crossover with passive limiter for the protection of the crossover, the LF-chassis and the HF-transducer
- due to a serially integrated transformer, the system is compatible for low-frequency operation as well as for connection to 100-V-systems
- rotary switch at front for the assignment of the operation mode (100-V-system / LF), i.e. operation mode and power adjustment can be determined after installation and cabling
- baffle and enclosure of heat-resistant ABS-synthetics according to UL 94V-0
- semi-gloss white perforated metal plate made of powder-coated steel, protected from falling by a special nylon rope
- enclosure of zinc-plated steel with a loop on the rear for additional safeguard mounting
- on the rear panel: 4-pin connector block for the connection of speakers and for the loop-through of signals to further speakers
- easy installation with enclosed mounting material (template for ceiling cutout, prolonged mounting angle for raster ceilings) for different mounting situations
- also furnished: special painting template for painting of the front frame

Technical specifications:

| | |
|----------------------------|----------------------|
| Frequency response (-3B) | 85 Hz to 18 kHz |
| Frequency response (-10dB) | 65 Hz to 20 kHz |
| Axial Sensitivity | 100dB (SPL 1W/1Mtr) |
| Maximum Calculated SPL | 126dB |



EVID

| | |
|--------|---------|
| Weight | 13.3 kg |
|--------|---------|

Make: Electro Voice or equivalent
Type: EVID C12.2
Delivery and mounting ready for operation

Make offered:

Type: