

Key Features:

- Enables use of Electro-Voice® Lavalier and Headworn Microphones in a Wired Configuration
- Designed for Vocal, Speech, and Instrument Use
- Selectable High-Pass Filter
- -10 dB Attenuation Switch
- Convenient, Optional Belt Clip



General Description:

The Electro-Voice® model TXA is a microphone accessory designed to enable the use of lavalier, head-worn, and other TA4F-terminated Electro-Voice professional microphones in a wired configuration. Powering microphones using standard phantom power through the TXA ensures the same high-quality audio performance that you expect using Electro-Voice microphones over wireless systems.

The selectable high-pass filter and -10dB pad allow the user to modify the performance of the microphone to suit each individual application.

Recommendations:

- Engage the -10dB pad for powerful vocals with head-worn microphones, or for close mic-ing high-SPL sound sources such as drum kits and musical instruments.
- Switch to 0 dB setting for lavalier microphones.
- Select the high-pass filter to reduce low-frequency ambient noise from HVAC systems, or whenever lower-frequency audio signals are undesirable.

Note: The TXA is designed specifically to function with Electro-Voice wireless microphones. The TXA will not function with other manufacturer's TA4F-terminated microphones.

Technical Specifications:

Frequency Response:	20 Hz - 20 kHz
Distortion (THD, 1 kHz):	<1% at -4.8 dBV (<1% at 4.7 dBV; -10 dB pad engaged)
Low-Frequency Roll-Off:	-6 dB at 100Hz
Attenuation:	0 or -10 dB at 1000 Hz
Power Requirements:	9 - 52 V Phantom Power
Connectors:	Input: TA4M Output: XLRM
TA4M Pinout:	Pin 1: Ground Pin 2: Microphone Signal Pin 3: +5VDC Bias Pin 4: Not Connected
Maximum Microphone Current Supply:	2.0 mA
Included Accessories:	Belt Clip
Color:	Black
Net Weight:	58.5 g (2.06 oz)



12000 Portland Avenue South, Burnsville, MN 55337
 Phone: 952/884-4051, Fax: 952/884-0043

www.electrovoice.com

© Telex Communications, Inc. 5/2007
 Part Number LIT000064 Rev C



U.S.A. and Canada only. For customer orders, contact Customer Service at:
800/392-3497 Fax: 800/955-6831

Europe, Africa, and Middle East only. For customer orders, contact Customer Service at:
+ 49 9421-706 0 Fax: + 49 9421-706 265

Other International locations. For customer orders, contact Customer Service at:
+ 1 952 884-4051 Fax: + 1 952 736-4212

For warranty repair or service information, contact the Service Repair department at:
800/553-5992 or 402/467-5321

For technical assistance, contact Technical Support at:

800/392-3497 or 952/736-4656

Specifications subject to change without notice.