RELESS





PRODUCT OVERVIEW

RE3 receivers and transmitters are available in 10 pre-packaged sets, configured to cover a wide range of performance and presentation applications. Sets contain one 1/2-rack-space diversity receiver with antennas, a universal power supply, a rack mount kit, a transmitter, batteries and an input device.

The RE3 operates on three bandwidths for the North American market, chosen to minimize the complexities of today's challenging RF environments. These include two 36 MHz-wide bands in the low and high 500 MHz spectrum, as well as one strategically chosen to operate within the 600 MHz duplex gap which the FCC has dedicated for wireless microphone use.

Key features

Professional-grade hardware

- Rack mountable ½-rack-space diversity receiver with rack mounting hardware
- · Five handheld transmitter sets with ND and RE series heads
- · Five bodypack transmitter sets with lavaliers, headworn and instrument cable options
- Robust aluminum handheld and cast magnesium bodypack transmitter bodies
- Easy-to-read LCD displays
- Recharging contacts on handheld and bodypack transmitters (can also be used with third party regular/rechargeable batteries)
- Battery charging station (optional accessory)
- Electro-Voice ND and RE series capsules on handheld transmitters
- Extensive selection of optional system accessories available
- Selectable high (50 mW) and low (10 mW) transmitter power (most bands)
- Broad selection of transmitter microphone types maximize application diversity
- Transmitters powered by common AA cells (battery level displayed on receiver)

User-friendly RF technology

- Clear frequency scanning
- · Wireless sync of transmitter to receiver
- · Keylock function protects settings from unwanted changes
- Diversity reception technology for trouble-free operation
- Wide selection of tuning bandwidths to help compensate for changing global RF regulations
- 36 MHz tuning bandwidths (most bands)
- Up to 1440 selectable frequencies
- Frequencies independently adjustable in 25 kHz steps
- Eight groups of pre-coordinated frequencies with up to 22 coordinated channels per group
- Simple multi-channel system setup

	F	B				013			0	(7.) 2 (2.) 10
	SET OPTIONS									
	RE3-ND76	RE3-ND86	RE3-ND96	RE3-RE420	RE3-RE520	RE3-BPOL	RE3-BPCL	RE3-BPHW	RE3-BPGC	RE3-BPNID
Handheld transmitter	•	•	•	•	•					
Microphone head	ND76	ND86	ND96	RE420	RE520					
Bodypack transmitter						•	•	-	•	-
Omnidirectional lavalier mic						•				
Cardioid lavalier microphone							•			
Headworn microphone								-		
Guitar cable									•	
1/2 space receiver	•	-	•	-	-		-	•	•	•

CONTAINS

Rack-mount hardware

		BAND OPTIONS			
		5L	5H	6M	
LS.	Bandwidth limits (MHz)	488 - 524	560 - 596	653 - 663	
DETAIL	Selectable frequencies	1440	1440	400	
	Output power (mW)	10 and 50	10 and 50	10 and 20	

RE3 wireless UHF diversity receiver I/O



Accessories



Battery charger

Active log periodic antenna

©2019 Bosch Security Systems, Inc. *Products shown on this page are not to scale

UHF antenna distribution system

