



America


# CERTIFICATE

No. U8V 09 03 10591 050

**Holder of Certificate:** EVI Audio GmbH

Hirschberger Ring 45  
94315 Straubing  
GERMANY

**Certification Mark:**



**Product:** Audio amplifiers  
(Audio Amplifier Module)

The product was voluntarily tested according to the relevant safety requirements and mentioned properties. It can be marked with the certification mark shown above. The certification mark must not be altered in any way. See also notes overleaf.

**Test report no.:** 68200900501

**Date,** 2009-04-08

Page 1 of 2





America

**CERTIFICATE**  
**No. U8V 09 03 10591 050**

**Model(s):** ZxA1; D 8A

**Brand Name:** EV or DYNACORD

**Parameters:**

Rated Input Voltage : 100-120VAC or 220-240VAC, 50-60 Hz  
 (Not user selectable,  
 see also remark)

Rated Power Input : 40W

Protection Class : I

Degree of Protection  
 against Ingress of  
 Dust and Liquid : IPX0

Remark :

- ZxA1 and D 8A are class I amplifier modules for building-in, consists of power supply board and amplifier board, can be loaded with one speaker with nominal impedance of 8ohm and one tweeter with nominal impedance of 8ohm.
- ZxA1 is identical to D 8A except model no., brand name and the size of front metal panel & plastic cover.
- The amplifier modules are built-in components, when installing the amplifier modules with their plastic cover into the end system, all requirements of relevant standard must be fulfilled.
- Rated input voltage of the module can be either 100-120VAC or 220-240VAC, which are set by manufacturer and cannot be adjusted by end user.
- All tests were performed in amplifier enclosure for D 8A with external dimension 44.2cm x 28.2cm x25.9cm (H x L x W) and internal volume about 0.2m<sup>3</sup>. The front panel and internal volume of other amplifier enclosure should not smaller than that for D8A.

**Tested according to:** UL 60065/R2006-11  
 CAN/CSA-C22.2 No. 60065:2003

**Production Facility(ies):** 67663

Page 2 of 2