

X-Line Compact XGS-3 Groundstack User Instructions



## XGS-3 Groundstack

The X-Line Compact Groundstack features a rigging attachment position to allow a column of an X-Line Compact Loudspeaker Array to be Groundstacked and tilted to obtain the desired sound coverage.



Figure 1: Attaching Loudspeakers to Groundstack Rails



To select the correct pin position on the bottom enclosure of your XLC Ground Stack, find your enclosure type and specific angle, and pin the Ground Stack swing arm to that position. For safety reasons, pin only to numerically indicated positions. Left sides are shown, right are mirrored views.

## Figure 2: Angle Instruction for Bottom Enclosure Pin Position



Figure 3: Full-Range Array -XLC127+ Array (8 Max) Figure 4: Subwoofer Array -XLC118 or XLC215 Array (5 Max) Figure 5: Combination Array -XLC127+ (5 Max) and XLC118/XLC215 (2 Max)

**Ev Electro<sup>1</sup>/olce<sup>®</sup>** 

12000 Portland Avenue South, Burnsville, MN 55337 Phone: 952/884-4051, Fax: 952/884-0043

www.electrovoice.com

© Telex Communications, Inc. 11/2005 Part Number 38110-464 Rev A U.S.A. and Canada only. For customer orders, contact the Customer Service department at 800/392-3497 Fax: 800/955-6831 Europe, Africa and Middle East only. For customer orders, contact the Customer Service department at 49 9421-706 0 Fax: 49 9421-706 265 For warranty information, contact the Service Repair department at: 616/695-6831 or 800/685-2606 For technical assistance, contact Technical Support at: 866/78AUDIO Specifications subject to change without notice.