



# EVA



High-power front loaded flying sub woofer

- 15" Low Frequency transducer.
- Very linear frequency response from 35Hz to 250Hz
- 18mm / 13 ply birch plywood with internal reinforced steel rigging hardware top and bottom.
- EVADA / LAPS Aiming and flying software
- Integrated Rigging hardware
- Concealed rigging hardware by side panels.
- White textured paint
- full-face protected by a powder-coated steel-front-grille backed with acoustic foam
- two multi pin phoenix connectors
- ANSI /IEC 60529 – IP55
- Maximum sustained humidity <80%
- Stainless steel grill and stainless steel Fasteners
- Single Amp channel powered design

Technical specifications:

Frequency response (-3dB):	48 Hz – 250 Hz
Frequency response (-10dB):	35 Hz – 250 Hz
Axial Sensitivity ( 1W/1Mtr)	98 dB
Maximum Calc. SPL	131 dB
Power Handling	500 W Cont / 2000W Peak
Nominal impedance	8 Ohms
Minimum impedance	5.3 Ohms
Connectors	Phoenix 10 AWG terminals
Dimensions	597 x 597 x 462 mm
Weight	max. 40.2 kg

Make: Electro Voice or equivalent  
 Type: EVA1151D PIW  
 Delivery and mounting ready for operation

Make offered: .....  
 Type: .....