



EVF

High-power front loaded flying sub woofer

- 12” Low Frequency front loaded bass element.
- Very linear frequency response from 48Hz to 156Hz
- 150W- 100V/70V Line transformer optional
- 13-ply birch plywood
- Black textured paint
- Stainless steel grill and stainless steel Fasteners
- full-face protected by a powder-coated steel-front-grille backed with acoustic foam
- two multi pin phoenix connectors
- ANSI /IEC 60529 – IP55
- Maximum sustained humidity <80%

Technical specifications:

Frequency response (-3dB):	66Hz – 100 Hz
Frequency response (-10dB):	48 Hz – 156 Hz
Axial Sensitivity (1W/1Mtr)	98 dB
Maximum Calc. SPL	130 dB
Power Handling	400 W Cont / 1600W Peak
Nominal impedance – Passive / Bi-amped	4 Ohms Passive 8 Ohms Bi-amped
Minimum impedance – Passive / Bi-amped	3.4 Ohms Passive 6.4 Ohms Bi-amped
Connectors	Phoenix 10 AWG terminals
Dimensions	768 x 470 x 467 mm
Weight	max. 26.2 kg

Make: Electro Voice or equivalent
 Type: EVF1121S PIB
 Delivery and mounting ready for operation

Make offered:
 Type: