



EVF

High-power front loaded flying sub woofer

- Dual 12" Low Frequency front loaded bass element.
- Very linear frequency response from 41Hz to 330Hz
- 13-ply birch plywood
- Black textured paint
- full-face protected by a powder-coated steel-front-grille backed with acoustic foam
- Two multi pin phoenix connectors
- ANSI /IEC 60529 – IP55
- Maximum sustained humidity < 95%
- Salt content of normal air exposure <70%
- Stainless steel grill and stainless steel Fasteners
- Single Amp channel powered design
- Fiberglass enclosure
- Direct exposure to sun and rain , heavy rain , fog & snow

Technical specifications:

Frequency response (-3dB):	54Hz – 145 Hz
Frequency response (-10dB):	41 Hz – 330 Hz
Axial Sensitivity (1W/1Mtr)	100 dB
Maximum Calc. SPL	135 dB
Power Handling	800 W Cont / 3200W Peak
Nominal impedance –	4 Ohms
Minimum impedance –	2.8 Ohms
Connectors	Phoenix 10 AWG terminals
Dimensions	768 x 470 x 467 mm
Weight	max. 37.4 kg

Make: Electro Voice or equivalent
 Type: EVF2121S FGB
 Delivery and mounting ready for operation

Make offered:
 Type: