



# EVF

High-power front loaded flying sub woofer

- Dual 12" Low Frequency front loaded bass element.
- Very linear frequency response from 41Hz to 330Hz
- 18mm / 13 ply birch plywood with internal reinforced steel rigging hardware top and bottom.
- White textured paint
- optional flying hardware
- Input phoenix panel to handle up to 10AWG connector
- 22 x 10M threaded suspension points
- 150W- 100V/70V Line transformer optional
- ANSI /IEC 60529 – IP44
- Maximum sustained humidity <80%
- Salt content of normal air <20%
- Galvanneal grill with vinyl coated acoustic screen and stainless steel Fasteners

Technical specifications:

Frequency response (-3dB):	54Hz – 145 Hz
Frequency response (-10dB):	41 Hz – 330 Hz
Axial Sensitivity ( 1W/1Mtr)	100 dB
Maximum Calc. SPL	135 dB
Power Handling	800 W Cont / 3200W Peak
Nominal impedance –	4 Ohms
Minimum impedance –	2.8 Ohms
Connectors	Phoenix 10 AWG terminals
Dimensions	768 x 470 x 467 mm
Weight	max. 37.4 kg

Make: Electro Voice or equivalent  
 Type: EVF2121S-WHT  
 Delivery and mounting ready for operation

Make offered: .....  
 Type: .....