



# EVID

Ultra compact, two-way full-range system with an appealing design, lightweight, also for outdoor use

- 2 x 3.5"- mid-bass-driver with a moisture-resistant special membrane in a vented enclosure
- 0.75"-titanium dometweeter with Neodymium magnet structure
- symmetrically located HF-section with Coherent Coverage Waveguide™ in combination with physically shaded woofers for minimized vertical lobing effects and improved vertical off-axis frequency response
- integrated crossover with passive limiter for the LF-chassis and the HF-driver
- the system is magnetically shielded and can be used near screens and monitors without any disturbances in the display
- ellipsoid enclosure constructed of acrylic butyl styrene (ABS)
- black ABS enclosure (the ABS has to be imbued to prevent changes to the colour in case of scratches)
- moisture- and weather-resistant to MIL-Spec 810, IEC 529 and IP 34 test conditions
- full-face protected by a powder-coated, zinc-plated grille, backed with acoustic fleece for the prevention of dust and moisture
- including robust, multi-axial Strong Arm Mount (SAM™)
- horizontal swing: 100°; vertical rotation: +/-45° (if the speaker is mounted with the long axis in the vertical plane)
- mounting bracket allows nearly invisible mounting, the final position can be fixed with two hexagon head screws
- additional safety point on rear side
- spring terminals for cable cross sections up to 4 mm<sup>2</sup>

## Technical specifications:

|   |                                      |
|---|--------------------------------------|
| Frequency response (-10dB)  | 85 Hz to 20 kHz                      |
| Nominal coverage (-6 dB)  | 120°H x 100°V                        |
| Maximum long-term average power-handling capacity (per IEC 268-5) | 75 W                                 |
| Sensitivity (1W/1m),  | 87 dB                                |
| Max. SPL (calc., full space) (1m)                                 | 108 dB                               |
| Nominal impedance   | 8 Ohm                                |
| Dimensions (W at front x H x D)                                   | max. 127 x 234 x 165 mm              |
| Weight  | max. 1.5 kg (incl. mounting bracket) |

Make: Electro Voice or equivalent  
 Type: EVID 3.2  
 Delivery and mounting ready for operation



# EVID



Make offered: .....

Type: .....