



# EVID

Ultra compact, two-way full-range system with an appealing design, lightweight, also for outdoor use, with a high-quality 70/100V - transformer

- 2 x 3.5" - mid-bass-driver with a moisture-resistant special membrane in a vented enclosure
- 0.75" -titanium dome tweeter with Neodymium magnet structure
- symmetrically located HF-section with Coherent Coverage Waveguide™ in combination with physically shaded woofers for minimized vertical lobing effects and improved vertical off-axis frequency response
- integrated crossover with passive limiter for the LF-chassis and the HF-driver
- the system is magnetically shielded and can be used near screens and monitors without any disturbances in the display
- transformer taps: 70V: 5W, 100V: 10W
- ellipsoid enclosure constructed of acrylic butyl styrene (ABS)
- black ABS enclosure (the ABS has to be imbued to prevent changes to the colour in case of scratches)
- moisture- and weather-resistant to MIL-Spec 810, IEC 529 and IP 34 test conditions
- full-face protected by a powder-coated, zinc-plated grille, backed with acoustic fleece for the prevention of dust and moisture
- including robust, multi-axial Strong Arm Mount (SAM™)
- horizontal swing: 100°; vertical rotation: +/-45° (if the speaker is mounted with the long axis in the vertical plane)
- mounting bracket allows nearly invisible mounting, the final position can be fixed with two hexagon head screws
- additional safety point on rear side
- spring terminals for cable cross sections up to 4 mm<sup>2</sup>

Technical specifications:

Frequency response (-10dB)	85 Hz to 20 kHz
Nominal coverage (-6 dB)	120°H x 100°V
Maximum long-term average power-handling capacity (per IEC 268-5)	10 W / 100 V 5 W / 70 V
Sensitivity (1W/1m),	87 dB
Max. SPL (calc., full space) (1m)	97 dB
Dimensions (W at front x H x D)	max. 127 x 234 x 165 mm
Weight	max. 1.5 kg (incl. mounting bracket)

Make: Electro Voice or equivalent  
 Type: EVID 3.2T  
 Delivery and mounting ready for operation



# EVID

Make offered: .....

Type: .....