



EVID

Compact, dual-voice-coil subwoofer with triangular-shaped enclosure

- 12"- high-excursion chassis with dual-voice-coil in a slot-loaded enclosure
- very high power capacity
- integrated passive crossover with a stereo input and stereo output with a high-pass crossover (6 dB/Oct.) for up to four satellites
- Ideal for combination with EVID™ 3.2 or EVID™ 4.2
- compact, triangular-shaped enclosure for corner mounting
- 16mm mediapan
- black textured paint
- including mounting bracket for quick and safe on-wall or corner mounting
- additional suspension insert for SAM™, safety point on rear side
- if a second 3/8"-eyebolt is used, the woofer can also be mounted "flying"
- available in black or white Futura™ coating
- surface can be repainted
- spring terminals for cable cross sections up to 4 mm²

Technical specifications:

Frequency response (-10dB):	40 Hz to 140 kHz
Nominal coverage	omni
Maximum long-term average power-handling capacity (per ANSI/EIA RS-426-A)	2x 175 W
Sensitivity (1W/1m),	100 dB
Max. SPL (calc., full space) (1W/1m)	125 dB
Nominal impedance	2x 8 Ohm
Dimensions (W at front x H x D)	max. 584 x 412 x 305 mm
Weight	max. 18.1 kg

Make: Electro Voice or equivalent

Type: EVID 12.1

Delivery and mounting ready for operation

Make offered:

Type: