



EVID

Ultra compact in-wall , two-way full-range system

- 2 x 4"- speaker system with polypropylene diaphragms for reliable and long term operation.
- One of the drivers has a 4" passive radiator coupled to dramatically extend the low frequency response.
- Extremely compact depth fits into tight spaces including walls and tight ceiling spaces.
- Titanium coated tweeter gives even uniform high frequency coverage.
- Full bandwidth overload protection.
- Front baffle wattage adjustment allows for easy level matching after installation.
- Easy four pin phoenix terminal
- Integrated 70V /100V transformer
- High temperature voice coil assemble
- Compact 100mm depth cabinet
- Ribbed rear back can for cabinet rigidity and to avoid cabinet flexing
- Four point quick mounting system

Technical specifications:

Frequency response (-3dB)	70 Hz to 20 kHz
Frequency response (-10dB)	52 Hz to 20 kHz
Nominal coverage (-6 dB)	150°
Maximum long-term average power-	50 W
Maximum peak power-	200 W
Sensitivity (1W/1m),	87 dB
Max. SPL (calc., full space) (1m)	110 dB
Nominal impedance	8 Ohm
HF transducer	1 inch
LF transducer	4 inch LF transducer / 4 inch passive radiator
Transformer taps 100V	3.75W / 7.5 W / 15 W / 30 W
Transformer taps 70V	1.75 W / 3.75W / 7.5 W / 15 W / 30 W
Dimensions (W at front x H x D)	max. 350 x 188 x 96.5 mm
Weight	max. 2.9 kg

Make: Electro Voice or equivalent

Type: FM4.2

Delivery and mounting ready for operation



EVID

Make offered:

Type: