



# EVID

## Ultra compact in-wall , two-way full-range system

- 2 x 6.5"- speaker system with polypropylene diaphragms for reliable and long term operation.
- One of the drivers has a 6.5" passive radiator coupled to dramatically extend the low frequency response.
- Extremely compact depth fits into tight spaces including walls and tight ceiling spaces.
- Titanium coated tweeter gives even uniform high frequency coverage.
- Full bandwidth overload protection.
- Front baffle wattage adjustment allows for easy level matching after installation.
- Easy four pin phoenix terminal
- Integrated 70V /100V transformer
- High temperature voice coil assemble
- Compact 100mm depth cabinet
- Ribbed rear back can for cabinet rigidity and to avoid cabinet flexing
- Four point quick mounting system

### Technical specifications:

Frequency response (-3dB)	60 Hz to 20 kHz
Frequency response (-10dB)	52 Hz to 20 kHz
Nominal coverage (-6 dB)	120°
Maximum long-term average power-	75 W
Maximum peak power-	300 W
Sensitivity (1W/1m),	90 dB
Max. SPL (calc., full space) (1m)	115 dB
Nominal impedance	8 Ohm
HF transducer	1 inch
LF transducer	6.5 inch LF transducer / 6.5 inch passive radiator
Transformer taps 100V	15 W / 30 W / 60 W
Transformer taps 70V	7.5 W / 15 W / 30 W / 60 W
Dimensions (W at front x H x D)	max. 465 x 256 x 10.3 mm
Weight	max. 5.8 kg

Make: Electro Voice or equivalent

Type: FM 6.2

Delivery and mounting ready for operation



# EVID

Make offered: .....

Type: .....