

DN9848 Preset Title: XLDBI-XSUB V1.0	
Notes: XL0201 BIAMP & XSE12. Do not adjust XSE201 output parameters - they are set for optimal line-array performance. Limiter thresholds set for P3000 with 0dBu for full output gain.	

INPUT CHANNELS		A	B	C	D
Gain	Gain (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
Delay	Delay (ms)	0 s	0 s	0 s	0 s
PEQ1	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ2	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ3	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ4	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ5	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ6	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ7	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ8	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ9	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ10	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ11	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ12	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB
Compressor	Threshold (dBu)	21.0 dBu	21.0 dBu	21.0 dBu	21.0 dBu
	Ratio (N To 1)	1 To 1	1 To 1	1 To 1	1 To 1
	Insert (In/Out)	Out	Out	Out	Out
	Attack (ms)	980 us	980 us	980 us	980 us
	Release (ms)	120 ms	120 ms	120 ms	120 ms
	Knee (Hard/Soft)	Soft	Soft	Soft	Soft
Name		Input A	Input B	Input C	Input D

Lock flags are only applied when a Preset is exported.

Inputs	Lock Flags
Gain	Unlocked
Delay	Unlocked
PEQs	Unlocked
Compressor	Unlocked
Name	Unlocked
Outputs	Lock Flags
Routing	Unlocked
Delay	Unlocked
Phase	Unlocked
Polarity	Unlocked
All Pass	Unlocked
LPF & HPF	Unlocked
PEQs	Unlocked
Limiter	Unlocked
Compressor	Unlocked
Gain	Unlocked
Names	Unlocked

OUTPUT CHANNELS		1	2	3	4	5	6	7	8
Routing	Source (A,B,C,D,A+B,C+D,A+B+C+D)	A	A	A	A	A	A	A	A
Delay	Delay (ms)	0 s	0 s	2.35 ms	0 s	0 s	0 s	2.35 ms	0 s
Phase	Phase Angle (degrees)	0°	0°	0°	0°	0°	0°	0°	0°
Reference (LFP, HPF, LPEQ1, PEQ2, PEQ3, PEQ4, PEQ5, PEQ6)	LFP	LFP	HPF	HPF	HPF	LFP	HPF	HPF	HPF
Invert	Invert (Yes/No)	No	No	No	No	No	No	No	No
All-Pass Filter	Frequency (Hz/kHz)	1.00 kHz	400 Hz	1.00 kHz	1.00 kHz	1.00 kHz	400 Hz	1.00 kHz	1.00 kHz
	Enable (On/Off, 1st, 2nd)	Off	1	Off	Off	Off	2nd	Off	Off
LPF	Q (No Units)	1	1	1	1	1	1	1	1
HPF	Frequency (Hz/kHz)	100 Hz	213 Hz	16.00 kHz	50.0 Hz	150 Hz	213 Hz	16.00 kHz	50.0 Hz
	Type (Bypass, Butter, Linkwitz-Riley)	24 dB/Octave Linkwitz-Riley	24 dB/Octave Bessel	24 dB/Octave Linkwitz-Riley	Full Range	24 dB/Octave Linkwitz-Riley	24 dB/Octave Bessel	24 dB/Octave Linkwitz-Riley	Full Range
LEQ/PEQ1	Frequency (Hz/kHz)	33.7 Hz	100 Hz	100 Hz	100 Hz	33.7 Hz	100 Hz	100 Hz	100 Hz
	Filter Type	24 dB/Octave Butterworth	24 dB/Octave Linkwitz-Riley	24 dB/Octave Linkwitz-Riley	Full Range	24 dB/Octave Butterworth	24 dB/Octave Linkwitz-Riley	24 dB/Octave Linkwitz-Riley	Full Range
LEQ/PEQ2	Frequency (Hz/kHz)	37.4 Hz	295 Hz	10.90 kHz	1.00 kHz	37.4 Hz	295 Hz	10.90 kHz	1.00 kHz
	Level (dB)	4.0 dB	-4.0 dB	7.0 dB	0.0 dB	4.0 dB	-4.0 dB	7.0 dB	0.0 dB
PEQ2	Frequency (Hz/kHz)	0.6 Oct	0.7 Oct	1.5 Oct	3.0 Oct	0.6 Oct	0.7 Oct	1.5 Oct	3.0 Oct
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ3	Frequency (Hz/kHz)	57.0 Hz	1.00 kHz	900 Hz	1.00 kHz	57.0 Hz	1.00 kHz	900 Hz	1.00 kHz
	Level (dB)	-2.7 dB	0.0 dB	-4.0 dB	0.0 dB	-2.7 dB	0.0 dB	-4.0 dB	0.0 dB
PEQ4	Frequency (Hz/kHz)	0.3 Oct	3.0 Oct	1.0 Oct	3.0 Oct	0.3 Oct	3.0 Oct	1.0 Oct	3.0 Oct
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB
PEQ5	Frequency (Hz/kHz)	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB	0.0 dB
HEQ/PEQ6	Frequency (Hz/kHz)	315 Hz	1.00 kHz	1.00 kHz	1.00 kHz	315 Hz	1.00 kHz	1.00 kHz	1.00 kHz
	Level (dB)	-0.0 dB	0.0 dB	0.0 dB	0.0 dB	-0.0 dB	0.0 dB	0.0 dB	0.0 dB
Compressor	Threshold (dBu)	21.0 dBu	21.0 dBu	21.0 dBu	21.0 dBu	21.0 dBu	21.0 dBu	21.0 dBu	21.0 dBu
	Ratio (N To 1)	1 To 1	1 To 1	1 To 1	1 To 1	1 To 1	1 To 1	1 To 1	1 To 1
Limiter	Insert (In/Out)	Out	Out	Out	Out	Out	Out	Out	Out
	Attack (ms)	5 ms	980 us	980 us	980 us	5 ms	980 us	980 us	980 us
Gain	Release (ms)	200 ms	120 ms	120 ms	120 ms	200 ms	120 ms	120 ms	120 ms
	Knee (Hard/Soft)	Hard	Soft	Soft	Soft	Hard	Soft	Soft	Soft
Look-Ahead Delay (ms)	Threshold (dBu)	2.0 dBu	0.0 dBu	-1.0 dBu	21.0 dBu	2.0 dBu	0.0 dBu	-1.0 dBu	21.0 dBu
	Release (ms)	100 ms	100 ms	100 ms	100 ms	100 ms	100 ms	100 ms	100 ms
Gain	Knee (Hard/Soft)	Hard	Hard	Hard	Hard	Hard	Hard	Hard	Hard
	Look-Ahead Delay (ms)	250.00 us	250.00 us	250.00 us	250.00 us	250.00 us	250.00 us	250.00 us	250.00 us
Name	Level (dB)	0.0 dB	-1.0 dB	0.0 dB	0.0 dB	-1.0 dB	-1.0 dB	-1.0 dB	0.0 dB
	Mute (On/Off)	Off	Off	Off	Off	Off	Off	Off	Off
Name		XSub	XSub LFP	XSub FR	XSub	XSub LFP	XSub FR	XSub	XSub