

### SUPERIOR ELECTRO-VOICE SOUND QUALITY AND FLEXIBLE FUNCTIONALITY - COMBINED IN A VERY COMPACT PACKAGE

The EVOLVE 30M is designed to deliver a significant step up in all-around performance for a column system in its size/price category. It is equipped with the most complete feature set in its class, including an eight-channel digital mixer, studio-quality onboard effects, and remote control of all audio, effects and mix functions via the next-generation Electro-Voice QuickSmart Mobile application. High-resolution, low-latency Bluetooth\* streaming ensures excellent results for music playback or accompaniment.

**MIX YOUR SHOW LIKE A PRO OPTIMIZE EVERY DETAIL OF YOUR SOUND ROOM-FILLING COVERAGE SUPER-QUICK SET UP** SINGLE-TRIP PORTABILITY

Ey/



# EVOLVE 30M



### **REFINED INDUSTRIAL DESIGN AND PROFESSIONAL-GRADE EV-ENGINEERED COMPONENTS**

The EVOLVE 30M sounds as good as it looks. The full-range column array and its six lightweight 2.8" neodymium drivers provide ultra-wide 120° coverage via proprietary waveguides; array-formed 40° asymmetrical vertical coverage ensures acoustic output is directed towards both sitting and standing audience members. A 10" subwoofer is housed in a 15 mm wood enclosure for enhanced rigidity and acoustical performance. A Class-D amplifier provides up to 1000 W of output power. The array and sub are connected via a two-piece symmetrical aluminum pole with internal wiring and magnetically assisted latching.

#### **INDUSTRY-LEADING QUICKSMART DSP**

(0)

QuickSmart DSP allows navigation of system parameters via an LCD with single-knob control or via the options for signal routing and inputs. Fu presets (Music, Live, Speech, Club), th (low, mid, high), seven-band graphic EC user-programmable presets (Store and power, visual monitoring of limiter status meters, and a master volume control to

#### **ONBOARD MIXER GIVES YOU BEST-IN-CLA CONNECTIVITY AND CONTROL**

Developed in collaboration with the electronics engineering team at EV' the integrated fully featured, fully co has multiple inputs with professiona functions. The mixer can be controll Mobile app or via the LCD/single-kr

#### FINESSE YOUR SOUND WITH MUSICIAN-FRIENDLY FEATURES

Independent channel aux sends and Hi-Z and foot switch inputs are included for flexible system configuration, and a range of onboard studio-quality effects (30 presets, including chorus, delay, flange and reverb, via two FX channels) add myriad options for musicians to fine-tune their tone - and reduce the amount of gear they need to bring to the gig. The onboard effects can be controlled via the QuickSmart Mobile app or via the LCD/singleknob interface.

The EVOLVE 30M joins the larger EVOLVE 50 in the awardwinning Electro-Voice EVOLVE column speaker system series.

## Eγ

#### **Electro-Voice**

e app, as well as multiple Functions include four		1x 1/4" foot switch input 1x XLR mix out output 1x XLR aux out output
hree-band system EQ EQ (in Mixer mode), five	Enclosure:	Column: composite Pole (2 pcs): aluminum Sub: 15 mm plywood
d Recall settings), phantom us, input level control and	Grille:	Steel with black or white powder coat
o optimize gain structure.	Color:	Black or white
LASS	Dimensions (HxWxD): mm (in)	Column: 620 x 95 x 157 (24.4 x 3.7 x 6.2) Pole (2 pcs): 600 x 48 x 55 (23.6 x 1.9 x 2.2) Sub: 448 x 332 x 432 (17.6 x 13.1 x 17)
e world-class audio /'s sibling brand Dynacord, onfigurable digital mixer al-grade preamps and mix lled via the QuickSmart anob interface.	Net weight:	Column: 6.0 lb (2.7 kg) Pole (2 pcs): 3.1 lb (1.4 kg) Sub: 34.9 lb (15.8 kg) Bag for column and pole: 1.9 lb (0.85 kg)
	Power consumption <sup>3</sup> :	100-240 V AC, 50-60 Hz, 1.5-0.6 A
	<sup>1</sup> Half-space measurement using live DSP preset. <sup>2</sup> Mavimum SPL is measured at 1 m using broadban <sup>3</sup> Current rating is 1/8 power.	d pink noise at maximum output.

4x XLR/TRS combo jack line/mic input 2x XLR/TRS combo jack for stereo line input

1x wireless stereo Bluetooth® audio input

1x 1/4" TRS Hi-Z input 1x stereo RCA input

1x 3.5 mm stereo input

App Store oogle Pla www.electrovoice.com/evolve30m

EV QuickSmart Mobile available in select countries. Apple, the Apple logo, iPhone®, iPad®, and App Store® are trademarks of Apple Inc., registered in the U.S. and other countries. Google Play and the Google Play logo are trademarks of Google LLC. \*Bluetooth® is available in select countries. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Bosch Security Systems, Inc. is under license. Other trademarks and trade names are those of their respective owners. ©2019 Bosch Security Systems

#### TECHNICAL SPECIFICATIONS

Frequency response (-3 dB)1: 51 Hz - 20 KHz

Frequency range (-10 dB)<sup>1</sup>: 45 Hz - 20 KHz

Maximum SPL<sup>2</sup>: 123 dB

Amplifier rating: 1000 W

LF channel rating: 500 W

HF channel rating: 500 W

Crossover frequency: 200 Hz

Connectors:

Coverage (H x V): 120° x 40°

Ey Electro-Voi EVOLVE 30M

0