



EVA



Compact two way passive line array speaker

- Two Way Passive true line array
- Each cabinet contains two individual controllable elements.
- 6th order passive internal networks.
- Four 1.25" titanium, compression drivers per cabinet. Mounted on Hydra plane wave generators and two wave guides.
- Two 8" LF woofers.
- EVADA / LAPS Aiming and flying software
- Integrated Rigging hardware
- Concealed rigging hardware by side panels.
- White textured paint
- full-face protected by a powder-coated steel-front-grille backed with acoustic foam
- Single Amp channel design
- Two multi pin phoenix connectors
- ANSI /IEC 60529 – IP44
- Maximum sustained humidity <80%
- Salt content of normal air <20%
- Galvanneal grill with vinyl coated acoustic screen and stainless steel Fasteners

Technical specifications:

| | |
|------------------------------|--------------------------|
| Frequency response (-3dB): | 60 Hz – 19Khz |
| Frequency response (-10dB): | 45 Hz – 20Khz |
| Nominal coverage H | 120° |
| Nominal coverage V | 20° |
| Hi Pass Filter | 50 Hz |
| Axial Sensitivity (1W/1Mtr) | 104 dB |
| Maximum Calc. SPL | 135 dB |
| Power Handling | 350 W Cont / 1400W Peak |
| Nominal impedance | 16 Ohms |
| Minimum impedance | 12 Ohms |
| Connectors | Phoenix 10 AWG terminals |
| Dimensions | 512 x 597 x 369 mm |
| Weight | max. 35.2 kg |

Make: Electro-Voice or equivalent
 Type: EVA 2082-1220-WHT

Delivery and mounting ready for operation

Make offered:

Type: