



EVA



High-power front loaded flying sub woofer

- Dual 15" Low Frequency transducers.
- Very linear frequency response from 28Hz to 200Hz
- 18mm / 13 ply birch plywood with internal reinforced steel rigging hardware top and bottom.
- EVADA / LAPS Aiming and flying software
- Integrated Rigging hardware
- Concealed rigging hardware by side panels.
- Black textured paint
- full-face protected by a powder-coated steel-front-grille backed with acoustic foam
- Single Amp channel design
- Two multi pin phoenix connectors
- ANSI /IEC 60529 – IP44
- Maximum sustained humidity <80%
- Salt content of normal air <20%
- Galvanneal grill with vinyl coated acoustic screen and stainless steel Fasteners

Technical specifications:

Frequency response (-3dB):	38 Hz – 200 Hz
Frequency response (-10dB):	28 Hz – 200 Hz
Axial Sensitivity (1W/1Mtr)	100 dB
Maximum Calc. SPL	130dB Cont / 136dB Peak
Power Handling	1000 W Cont / 4000W Peak
Crossover Frequencies	80Hz – 125Hz (100Hz Typical)
Nominal impedance	4 Ohms
Minimum impedance	2.8 Ohms
Connectors	Phoenix 10 AWG terminals
Dimensions	930 x 597 x 792 mm
Weight	max. 80.8 kg

Make: Electro Voice or equivalent

Type: EVA2151D-BLK

Delivery and mounting ready for operation

Make offered:

Type: