



High-power front loaded flying subwoofer

- 18" low frequency front loaded bass element with 2.5" voice coil
- Electrical compensation network that responds to the drive signal by modifying the response of an integral high-pass filter when an inline transformer is installed in the loudspeaker, in order to minimize transformer saturation and protect system electronics
- 15-mm plywood enclosure
- Black textured paint
- (8) M10 suspension points and optional flying hardware
- Input phoenix panel to handle up to 10AWG connector
- Input panel has an internal landing pad for 70V/100V operation
- ANSI / IEC 60529 – IP44
- Maximum sustained humidity 80%
- Salt content of normal air < 20%
- 18 GA powder-coated cold-rolled steel front grill backed with acoustically transparent fabric

Technical specifications:

Frequency response (-3dB):	38 Hz – 95 Hz
Frequency response (-10dB):	30 Hz – 135 Hz
Axial Sensitivity ( 1W/1m)	97 dB
Maximum Calc. SPL	129 dB
Power Handling	400 W Cont / 1600W Peak
Nominal impedance	8 Ohms
Minimum impedance	6.3 Ohms
Connectors	Dual four-pin 10 AWG Phoenix / Euro Block screw-terminals
Dimensions (H x W x D)	(503 x 554 x 718) mm
Weight	max. 32.6 kg

Make: Electro-Voice or equivalent  
 Type: EVC-1181S-B  
 Delivery and mounting ready for operation

Make offered: .....  
 Type: .....