



EVF

Two-way, high-power full-range system for active or passive operation with an asymmetric CD-horn

- 12" Low Frequency transducer using FEA optimized woofer.
- 2" titanium compression driver with 1.4"-throat diameter.
- Rotatable 12" x 12" CD horn.
- Very linear frequency response from 56 Hz to 20 kHz, max. deviation from linearity: +/- 2 dB
- Advanced 4th Order Crossover 24 db octave Slope with HF protection
- Integrated crossover with an acoustic crossover frequency of 1,450 Hz
- dynamic protection circuit for independent protection of both ways against thermal overload
- switchable bi-amp or passive operation:
- compact, trapezoidal-shaped,
- 13-ply birch plywood
- white textured paint
- optional flying hardware
- Input phoenix panel to handle up to 10AWG connector
- Easy external operation mode selection switch
- full-face protected by a powder coated steel front grille backed with acoustic foam
- ANSI /IEC 60529 – IP55
- Maximum sustained humidity < 95%
- Salt content of normal air exposure <70%
- Stainless steel grill and stainless steel Fasteners
- Fiberglass enclosure
- Direct exposure to sun and rain , heavy rain , fog & snow

Technical specifications:

| | |
|------------------------------|--------------------------|
| Frequency response (-3dB): | 56 Hz – 20Khz |
| Frequency response (-10dB): | 45 Hz – 20Khz |
| Nominal coverage H | 90° - rotatable |
| Nominal coverage V | 90° - rotatable |
| Crossover Frequency | 1450 Hz |
| Axial Sensitivity (1W/1Mtr) | 98 dB |
| Maximum Calc. SPL | 125 dB |
| Power Handling | 500 W Cont / 2000W Peak |
| Nominal impedance | 8 Ohms |
| Minimum impedance | 6 Ohms |
| Connectors | Phoenix 10 AWG terminals |
| Dimensions | 769 x 409 x 414 mm |
| Weight | max. 28.1 kg |



EVF

Make: Electro Voice or equivalent
Type: EVF1122-S 99 FGW
Delivery and mounting ready for operation

Make offered:
Type: