



EVF

Two-way, high-power full-range system for active or passive operation with an asymmetric CD-horn

- 15" Low Frequency transducer using FEA optimized woofer.
- 2" titanium compression driver with 1.4"-throat diameter.
- Rotatable 12" x 12" CD horn.
- Very linear frequency response from 41 Hz to 18 kHz, max. deviation from linearity: +/- 2 dB
- Advanced 4th Order Crossover 24 db octave Slope with HF protection
- integrated crossover with an acoustic crossover frequency of 1,450 Hz
- dynamic protection circuit for independent protection of both ways against thermal overload
- switchable bi-amp or passive operation:
- compact, trapezoidal-shaped,
- 13-ply birch plywood
- optional flying hardware
- black textured paint
- input phoenix panel to handle up to 10AWG connector
- Easy external operation mode selection switch
- full-face protected by a powder coated steel front grille backed with acoustic foam
- ANSI /IEC 60529 – IP55
- Maximum sustained humidity < 95%
- Salt content of normal air exposure <70%
- Stainless steel grill and stainless steel Fasteners
- Fiberglass enclosure
- Direct exposure to sun and rain , heavy rain , fog & snow

Technical specifications:

| | |
|------------------------------|--------------------------|
| Frequency response (-3dB): | 70 Hz – 19Khz |
| Frequency response (-10dB): | 44 Hz – 20Khz |
| Nominal coverage H | 60° - rotatable |
| Nominal coverage V | 60° - rotatable |
| Crossover Frequency | 1450 Hz |
| Axial Sensitivity (1W/1Mtr) | 100 dB |
| Maximum Calc. SPL | 127 dB |
| Power Handling | 500 W Cont / 2000W Peak |
| Nominal impedance | 8 Ohms |
| Minimum impedance | 6 Ohms |
| Connectors | Phoenix 10 AWG terminals |
| Dimensions | 769 x 471 x 465 mm |
| Weight | max. 32 kg |



EVF

Make: Electro Voice or equivalent
Type: EVF1152-S 66 FGB
Delivery and mounting ready for operation

Make offered:
Type: