



# EVF

High-power front loaded flying sub woofer

- 18” Low Frequency front loaded bass element.
- Very linear frequency response from 28Hz to 650Hz
- 13-ply birch plywood
- Black textured paint
- full-face protected by a powder-coated steel-front-grille backed with acoustic foam
- Two multi pin phoenix connectors
- ANSI /IEC 60529 – IP55
- Maximum sustained humidity < 95%
- Salt content of normal air exposure <70%
- Stainless steel grill and stainless steel Fasteners
- Single Amp channel powered design
- Fiberglass enclosure
- Direct exposure to sun and rain , heavy rain , fog & snow

Technical specifications:

Frequency response (-3dB):	35Hz – 100 Hz
Frequency response (-10dB):	28 Hz – 650 Hz
Axial Sensitivity ( 1W/1Mtr)	99 dB
Maximum Calc. SPL	131 dB
Power Handling	400 W Cont / 1600W Peak
Nominal impedance –	8 Ohms
Minimum impedance –	6 Ohms
Connectors	Phoenix 10 AWG terminals
Dimensions	768 x 675 x 726 mm
Weight	max. 46 kg

Make: Electro Voice or equivalent  
 Type: EVF1181S FGB  
 Delivery and mounting ready for operation

Make offered: .....  
 Type: .....