



EVF

High-power front loaded flying sub woofer

- Dual 15" Low Frequency front loaded bass element.
- Very linear frequency response from 41Hz to 330Hz
- 18mm / 13 ply birch plywood with internal reinforced steel rigging hardware top and bottom.
- White textured paint
- optional flying hardware
- Input phoenix panel to handle up to 10AWG connector
- 22 x 10M threaded suspension points
- 150W- 100V/70V Line transformer optional
- ANSI /IEC 60529 – IP44
- Maximum sustained humidity <80%
- Salt content of normal air <20%
- Galvanneal grill with vinyl coated acoustic screen and stainless steel Fasteners

Technical specifications:

Frequency response (-3dB):	40Hz – 2600 Hz
Frequency response (-10dB):	30 Hz – 3200 Hz
Axial Sensitivity (1W/1Mtr)	101 dB
Maximum Calc. SPL	137 dB
Power Handling	1000 W Cont / 4000W Peak
Nominal impedance –	4 Ohms
Minimum impedance –	2.7 Ohms
Connectors	Phoenix 10 AWG terminals
Dimensions	768 x 675 x 726 mm
Weight	max. 53.1 kg

Make: Electro Voice or equivalent
 Type: EVF2151D-WHT
 Delivery and mounting ready for operation

Make offered:
 Type: