


<u>Ultra compact, two-way full-range system with an appealing design, lightweight, also</u> for outdoor use, with a high-quality 70/100V transformer

- 2 x 4"- mid-bass-driver with a moisture-resistant special membrane in a vented enclosure
- high-frequency driver with Neodymium magnet structure and 1"-titanium diaphragm, mounted on a Coherent Coverage Waveguide horn with 1"-throat diameter
- symmetrically located HF-section in combination with physically shaded woofers for minimized vertical lobing effects and improved vertical off-axis frequency response
- integrated crossover with passive limiter for the LF-chassis and the HF-driver
- the system is magnetically shielded and can be used near screens and monitors without any disturbances in the display
- transformer taps: 70V: 7.5/15/30W; 100V: 7.5/15/30W
- ellipsoid enclosure constructed of acrylic butyl styrene (ABS)
- white ABS enclosure (the ABS has to be imbued to prevent changes to the colour in case of scratches)
- moisture- and weather-resistant to MIL-Spec 810, IEC 529 and IP 34 test conditions
- full-face protected by a powder-coated, zinc-plated grille, backed with acoustic fleece for the prevention of dust and moisture
- including stable, multi-axial Strong Arm Mount (SAMTM)
- horizontal swing: 100°; vertical rotation: +/-45° (if the speaker is mounted with the long axis in the vertical plane)
- mounting bracket allows nearly invisible mounting, the final position can be fixed with two hexagon head screws
- additional safety point on rear side
- spring terminals for cable cross sections up to 4 mm²

Technical specifications:

Frequency response	65 Hz to 20 kHz
(-10dB)	
Nominal coverage (-6 dB)	100°H x 90°V
Maximum long-term average power-	30 W / 100 V
handling capacity (per IEC 268-5)	
Sensitivity (1W/1m),	89 dB
Max. SPL (calc., full space) (1m)	104 dB
Dimensions (W at front x H x D)	max. 175 x 310 x 216 mm
Weight	max. 3.9 kg (incl. mounting bracket)

Make: Electro Voice or equivalent



Type: E	VID 4.2TW
Delivery and mounting ready	y for operation
, ,	•
Make offered:	
wake offered.	
T	
Type:	