



# EVID

## Co-axial 2-way Ceiling Speaker System

- 100 mm (4") mid-bass driver with a moisture-resistant special membrane in a vented enclosure
- 19 mm (0.75") swivel HF-transducer with titanium coating and a horn in co-axial array for symmetric coverage
- linear frequency response and conic, very wide and even coverage
- integrated crossover with passive limiter for the protection of the crossover, the LF-chassis and the HF-transducer
- due to a serially integrated transformer, the system is compatible for low-frequency operation as well as for connection to 100-V-systems
- rotary switch at front for the assignment of the operation mode (100-V-system / LF), i.e. operation mode and power adjustment can be determined after installation and cabling
- baffle and enclosure of heat-resistant ABS-synthetics according to UL 94V-0
- semi-gloss white perforated metal plate made of powder-coated steel, protected from falling by a special nylon rope
- enclosure of zinc-plated steel with a loop on the rear for additional safeguard mounting
- on the rear panel: 4-pin connector block for the connection of speakers and for the loop-through of signals to further speakers
- easy installation with enclosed mounting material (template for ceiling cutout, prolonged mounting angle for raster ceilings) for different mounting situations
- also furnished: special painting template for painting of the front frame

### Technical specifications:

Frequency response (-10dB)	65 Hz to 20 kHz
Nominal coverage (-6 dB)	130° (conic)
Maximum long-term average power-handling capacity (per IEC 268-5)	80 W
Sensitivity (1W/1m),	86 dB
Max. SPL (1m)	110 dB
Nominal impedance	8 Ohm (transformer bypass)
Transformer taps	100V: 3.75, 7.5, 15 or 30W Bypass: 8 Ohm
Dimensions (H x Ø)	176 x 181 mm (front panel : 210 mm)
Cutout size	184 mm
Weight	2.7 kg

Make: Electro Voice or equivalent  
 Type: EVID C4.2



# EVID

Delivery and mounting ready for operation

Make offered: .....

Type: .....